



Pro

High Flow with premium membrane innovated to maximize flow rates

Flow [litres/day]	Flow [USGAL/day]	Recovery [%]
6912	1826	61.1

Technical Properties

Product Identifiers

Product name	Pro
Product code	Pro 400C HF

Purification Technology

SuperiorOsmosis™

China

Product number	919240142
Voltage	230V~ 50/60 Hz
Power consumption [W]	530
Plug / Type	Grounded Chinese / I

Europe

Product number	919240162
Voltage	230V~ 50/60 Hz
Power consumption [W]	530
Plug / Type	Grounded European / F

UK

Product number	919240181
Voltage	230V~ 50/60 Hz
Power consumption [W]	530
Plug / Type	Grounded UK / G

US

Product number	919240150
Voltage	120V~ 60 Hz
Power [Amps]	6
Plug / Type	Grounded American / B

Dimension W x D x H

Product dimension [mm]	225 x 430 x 466
Product dimension [inch]	8.9 x 16.9 x 18.3
Installation dimension [mm]	225 x 460 x 466
Installation dimension [inch]	8.9 x 18.1 x 18.3

Weight

29 kg / 64 lbs packaged weight

Prefiltration

Particle and Granulated Activated Carbon (GAC) prefilter

Activation Type

Pressure controlled (On / Off, 3 / 4.5 [bar])

Faucet

Faucet included on some markets (China and US). Customized faucet must be suitable for RO-water.

Features

Low pressure protection stop	Yes
Low pressure protection automatic restart	Yes

Features

Run time meter	Yes
Water quality indicator	Yes
Water quality alarm	Yes
Water quality stop	Yes
Suitable for brackish water	No
Clean water rinse valve	No
Compatible with household appliances	Yes

Requirements of Inlet Water

Pressure [psi]	29-145
Flow [l/min]	>10
TDS [mg/l]	<1500
Conductivity [µS/cm, 25 °C]	<2000
Temperature	2-35 [°C] / 35.6-95 [°F]
Hardness [mg/l]	<200
Iron Fe(II) [mg/l]	<1.5
Iron Fe(III) [mg/l]	<0.3
Turbidity [FNU]	<0.5

Maintenance

Recommended frequency between membrane/filter change

Sediment prefilter	4-6 months
Granulated Activated Carbon prefilter	4-6 months
High Flow Membrane	4-6 years

Reduction Performance

Pro has passed reduction performance test according to NSF 58 for below listed substances

Salt Rejection [TDS]	95.3%
Lead	99.7%
Chromium (III)	99.5%
Arsenic (V)	99.3%

